

THRII® TAP+ HAND WASH DRYER INSTALLATION INSTRUCTIONS

Thrii-Tap+ D

ISSUE 1



1

NOTICES

Please ensure you read these notes before you start to install the product

- All electrical work must be carried out by a qualified electrician and should be installed in accordance with the current Nationally Approved Regulations (For UK I.E.E.)
- This appliance must be earthed.
- Do not switch on electric supply to unit with control module covers removed.
- Risk of electric shock, serious injury or death. Only qualified personnel should remove the cover of the control module when powered up.

4

MOUNTING SURFACE PREPARATION

1. Measure, mark and core a hole through basin or vanity to the dimensions shown in figure 3.
2. Take note of the required clearance as shown in figure 4.




Fig 3




Fig 4


2

PACKAGE CONTENTS

Your package should contain the following contents.

If any of these items are missing please contact Wallgate for details see section 12.


a) 1 Tap Head Assembly



b) 1 Installation Instructions



c) 1 Air hose – with 2 jubilee clips




d) 2 Cable ties and earth cable



e) Sensor cable shroud



f) 1 Soap bracket



g) 1 Control Module



h) 1 Container of liquid soap (2.5 litres)




Fig 1

5

MOUNTING THE TAP HEAD

1. Remove 2x M6 nuts and mounting bracket from tap head.
2. Carefully pass tap head hoses through hole made in basin or vanity before seating washer and tap onto deck as per figure 5.
3. Then thread the mounting bracket over to hoses. Position the mounting bracket over the tap assembly and align with the two M6 threaded rods. Secure into position using the M6 nuts and tighten by hand see figure 6.
4. Check the orientation of the tap head is correctly positioned over the basin. Once this is in position gradually tighten each nut equally to 5Nm.
5. Remove earth screw and shakeproof washers. Fit earth cable ring terminal between washers and tighten screw back into bracket to earth tap.




Fig 6





Fig 5


3

TOOLS REQUIRED


a) Screwdrivers



b) 10mm spanner




c) 23mm spanner




d) Drill



e) Hole saw



f) Tools/drill bits to suit wall and fixings



g) Cleaning materials



Fig 2

6

SOAP BRACKET MOUNTING

The soap hook can be installed remotely from the control module in a position convenient for access, and within space constraints. 0.6m of soap tube is supplied for connection between the soap bottle and the module.

The soap hook must be fastened to the wall with appropriate fasteners for the wall material (to be supplied by others).




Fig 7





Fig 8



7

CONTROL MODULE MOUNTING

The module is to be mounted to a flat sturdy wall via the mounting tabs. These are bi-directional slotted for ease of installation regardless of the module's orientation.

1. Remove the control module from the box.
2. Fasten to the wall using mounting hardware suitable for the wall material (to be provided by others). The wall must be robust enough to support the weight of the module. See figure 10




Fig 9




Fig 10

8

TAP CONNECTION TO CONTROL MODULE

1. Attach the air hose into position on the module. Secure using the jubilee clips provided.
2. Connect the flexi hose to the module "water outlet" by hand. Tighten with a 23mm spanner (figure 13).
3. Connect the M8 sensor cable to "sensor connection" on module. Align pins, tighten by hand and secure the shroud using the fixing provided (figure 15).
4. Attach 2x soap hoses to the "soap and air outlets" on the module. Use 2x cable ties to secure soap tube onto outlet spigots (figure 14).
5. Fit the earth cable from the tap head bracket to the earthing point on the right hand bracket of the control module.




Fig 11




Fig 12




Fig 13




Fig 14




Fig 15

9

CONTROL MODULE CONNECTION TO UTILITIES

The hand wash unit can be used with various water input methods with all internal components suitable for contact with water up to 60°C.

The water temperature is not controlled by the control module therefore a suitable temperature control system must be fitted before the module that is in line with local regulations.

Alternatively, the unit can be operated as cold water only, by directly connecting the module to a cold-water supply.

The unit should be fitted after an isolating valve to allow for ease of maintenance and installation.

1. To connect the module to the water supply simply screw on half a 1/2" BSP connector to the "water inlet" detailed in fig 11.
2. Ensure the module is connected to a main electrical supply via 13A socket or switched fuse spur.



Warning! All electrical work must be carried out by a qualified electrician and should be installed in accordance with the current nationally approved regulations.




Fig 16

Water Supply	
Minimum Pressure	1 Bar / 100KPa / 14.5 psi
Maximum Pressure	10 Bar / 1000KPa / 145 psi
Electrical Power Requirement	
220 - 240V 50/ 60Hz Single phase	
0.9 kW / 13A UK Switched Socket	

10

CONNECTING THE SOAP

1. Remove the soap container from the box.
2. Place the soap container onto the soap bracket to the right of the control module, ensuring the cap is outermost (See figure 17a).
3. Unscrew the cap from the soap container.
4. Replace cap with the push-fit cap pre-connected to the soap tube (See figure 17b).
5. Press the soap prime switch until soap is dispensed from the tap head (See figure 18).
6. Use the soap rocker switch to select the desired foam or liquid soap setting.
7. Replace the control module cover.
8. The unit is now ready for operation.



IMPORTANT! Only use soap recommended by Wallgate




Fig 17a




Fig 17b




Fig 18

11

COMMISSIONING/HANDOVER

1. Ensure the control module cover panels are securely fitted and the electrical plug is securely connected to the socket
2. Inspect all connections on the top of the unit to make sure the soap, water, air, and sensor connections are secure and seated correctly.
3. Fully open the mains water supply isolating tap. Check the incoming water connections for leaks.
4. Switch ON the power to the unit, this will power-up the Wallgate Thrii-Tap+ ready for use.
5. Upon initial power-up, the Wallgate Thrii-Tap+ automatically runs through a 15-second water calibration cycle.
6. Ensure no leaks have occurred around the connections between the control module and the tap head.
7. Check the wash & dry cycle operates correctly and repeat the cycle at least five times.
8. Wipe sensor and nozzles using a soft cloth and non-abrasive cleaner and clean all surfaces




Fig 19

12

CARE, MAINTENANCE AND REPAIR

Any service or repair work must be done by a qualified engineer. During the warranty period, the service or repair must only be done by a Wallgate engineer or appointed service agent. Refer to the Wallgate terms and conditions for warranty information.

Replacement soap can be purchased directly from Wallgate, See contact details below.

For information on cleaning, maintenance and spares, a concise product manual is available on our web site www.wallgate.com. Alternatively, you can contact Wallgate directly, see details below.



Wallgate Limited, Crow Lane, Salisbury, Wiltshire SP2 0HB, England Wallgate is a registered trademark of Wallgate Limited.